



SAFETY DATA SHEET

SECTION 1	PRODUCT AND COMPANY IDENTIFICATION
Trade Name:	Muriate of Potash (MOP), all grades
Chemical Name:	Potassium Chloride
CAS Number:	7447-40-7
Chemical Family:	Inorganic Salt
Synonyms:	Potash MOP Potassium Chloride Potassium Muriate Potassium Monochloride Muriate of Potash
Primary Use:	Crop nutrient; Industrial applications
Company Information:	The Mosaic Company 101 East Kennedy Blvd, Ste 2500 Tampa, FL 33602 www.mosaicco.com (800) 918-8270 or (813) 775-4200 8 AM to 5 PM Eastern Time USA
Emergency Telephone:	EMERGENCY OVERVIEW 24 Hour Emergency Telephone Number: <u>For Chemical Emergencies:</u> Spill, Leak, Fire or Accident Call CHEMTREC North America: (800) 424-9300 (reference CCN201871) Others: (703) 527-3887 (collect)

SECTION 2	HAZARD IDENTIFICATION	
GHS Classification:	Not Applicable	Not Applicable
	Signal Word: not applicable Hazard Statement(s) Not applicable	
Label Elements:		
Prevention:	Not applicable	
Response:	Not applicable	Not applicable
	Not applicable	Not applicable
Storage:	Not applicable	Not applicable
Disposal:	Not applicable	Not applicable
Other Hazards which do not require classification:	Handling and/or processing of this material may generate dust which can cause mechanical irritation of the eyes, skin, nose and throat.	



SECTION 3	COMPOSITION INFORMATION ON INGREDIENTS			
Formula:	KCl			
Composition:	Potassium Chloride Sodium Chloride	CAS 7447-40-7 CAS 7647-14-5	95-99.5% 0.3-3.7%	

SECTION 4	FIRST AID MEASURES		
First Aid Procedures:	Eyes:	Move victim away from exposure and into fresh air. Flush eyes with plenty of clean water for at least 15 minutes. If symptoms persist, seek medical attention.	
	Skin:	Wash contaminated area thoroughly with mild soap and water. If chemical or solution soaks through clothing, remove clothing and wash contaminated skin. If irritation develops and persists after washing, seek medical attention.	
	Inhaled:	If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention.	
	Ingestion:	If large amounts are swallowed, seek emergency medical attention. If possible, do not leave victim unattended and observe closely for adequacy of breathing.	
Note to Physician:	None Known		

SECTION 5	FIRE FIGHTING MEASURES
Extinguishing Media:	Use extinguishing agent suitable for type of surrounding fire.
Protection of Firefighters:	<p>No unusual fire or explosion hazards are expected. When this material is subjected to high temperatures, it may release small amounts of chloride gas.</p> <p>Positive pressure, self-contained breathing apparatus is required for all firefighting activities involving hazardous materials. Full structural firefighting (bunker) gear is the minimum acceptable attire. The need for proximity, entry, flashover and/or special chemical protective clothing (see Section 8) needs to be determined for each incident by a competent firefighting safety professional.</p> <p>Water used for fire suppression and cooling may become contaminated. Discharge to sewer system(s) or the environment may be restricted, requiring containment and proper disposal of water (see Section 6).</p>

SECTION 6	ACCIDENTAL RELEASE MEASURES
Response Techniques:	Stay upwind and away from spill (dust hazard). Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). Prevent spilled material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways. Notify appropriate federal, state, and local agencies as may be required (see Section 15). Minimize dust generation. Sweep up and package appropriately for disposal. Large spills can harm or kill vegetation.



SECTION 7	HANDLING AND STORAGE
Handling:	The use of appropriate respiratory protection is advised when concentrations exceed any established exposure limits (see Section 8). Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing or shoes. Use good personal hygiene practices.
Storage:	Use and store this material in dry, well-ventilated areas. Store only in approved containers. Keep container(s) tightly closed. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage. Material may absorb moisture from the air.

SECTION 8	EXPOSURE CONTROLS / PERSONAL PROTECTION	
Engineering Controls:	Use process enclosure, general dilution ventilation or local exhaust systems where necessary to maintain airborne dust concentration below the OSHA standards or in accordance with applicable regulations.	
Personal Protective Equipment (PPE):	Eye/Face:	Approved eye protection to safeguard against potential eye contact, irritation, or injury is recommended.
	Skin:	The use of cloth or leather work gloves is advised to prevent skin contact, possible irritation and absorption.
	Respiratory:	A NIOSH approved air purifying respirator with a type 95 (R or P) particulate filter may be used under conditions where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed if workplace conditions warrant a respirator.
	Other:	A source of clean water should be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.
General Hygiene Considerations:	Wash thoroughly after handling Use adequate ventilation	
Exposure Guidelines:	OSHA Permissible Exposure Limits (PEL):	Particulates Not Otherwise Regulated: 5 mg/m ³ TWA (respirable); 15 mg/m ³ TWA (total)
	ACGIH Threshold Limit Value (TLV):	Particulates Not Otherwise Specified: 3 mg/m ³ TWA (respirable); 10 mg/m ³ TWA (inhalable)

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES
Note: Unless otherwise stated, values in this section are determined at 20°C (68°F) and 760 mm Hg (1 atm).	



Appearance:	White to reddish-brown, crystalline or granular	Vapor Pressure (mm Hg):	Not applicable
Odor:	None/Strong Saline	Vapor Density (air=1):	Not applicable
Odor Threshold:	No data available	Specific Gravity or Relative Density:	1.986 - 1.990
Physical state:	Solid	Bulk Density:	Loose 64 - 75 lbs/ft ³ (1025 - 1200 kg/m ³);
pH:	5.4 – 10.0 in a 5% solution	Solubility in Water:	99.5 - 99.999%; 34.2 g/100mL at 20°C
Melting Point/ Freezing Point:	772 to 776°C (1423 to 1428°F)	Partition coefficient:	No data available
Boiling Point:	Sublimes at 1500°C (2732°F)	Auto-Ignition Temperature:	Not applicable
Flash Point:	Not applicable	Decomposition Temperature:	No data available
Evaporation Rate:	No data available	Viscosity:	No data available
Flammability:	Not applicable	Volatility:	Not applicable
Upper/lower Flammability or explosive limits	Not applicable		

SECTION 10	STABILITY AND REACTIVITY
Chemical Stability:	Stable under normal conditions of storage and handling. Material is hygroscopic (May absorb moisture from air when relative humidity >72%).
Conditions to Avoid:	None known
Incompatible Materials:	Strong oxidizing agents, strong acids
Hazardous Decomposition Products:	None known
Corrosiveness:	Similar to salt. Mildly corrosive to metals in the presence of moisture.
Hazardous Polymerization:	Will not occur

SECTION 11	TOXICOLOGICAL INFORMATION		
Substance:	Potassium Chloride		
Acute Oral Toxicity:	LD ₅₀ (rat, oral) > 2600 mg/kg LD ₅₀ (mouse, oral) > 1500 mg/kg		
Acute Inhalation Toxicity:	No data available		
Acute Dermal Toxicity:	No data available		
Substance:	Sodium Chloride		
Acute Oral Toxicity:	LD ₅₀ (rat, oral) > 3000 mg/kg LD ₅₀ (mouse, oral) > 4000 mg/kg		
Acute Inhalation Toxicity:	LC ₅₀ (rat) > 42 g/m ³ / 1 hour		
Acute Dermal Toxicity:	No data available		
Mutagenesis:	No data available	Target Organ	No data available
Developmental Toxicity:	No data available	Carcinogenicity	No data available




SECTION 12	ECOLOGICAL INFORMATION
Ecotoxicology:	Dissolution of large quantities of potassium chloride and sodium chloride in water may create an elevated level of salinity that may be harmful to fresh water aquatic species and to plants that are not salt-tolerant. Potassium Chloride: Lepomis macrochirus LC50 - 2010 mg/l Physa heterostrapha LC50 - 940 mg/l Scenedesmus subspicatus EC50 - 2500 mg/l Sodium Chloride: Ceriodaphnia dubia LC50 - 280,000 - 3,540,000 ug/l Daphnia magna LC50 - 3,144,000 - 10,000,000 ug/l Daphnia pulex EC50 - 56.40 mM Pimephales promelas LD50 - 6,020,000 - 10,000,000 ug/l

SECTION 13	DISPOSAL CONSIDERATIONS
	This material, if discarded as produced, is not an RCRA "listed" or "characteristic" hazardous waste. Contamination may subject it to hazardous waste regulations. It is the generator's responsibility to properly characterize all waste materials. Consult federal, state/provincial and local regulations regarding the proper disposal of this material.

SECTION 14	TRANSPORT INFO	
Regulatory Status:	Not regulated	
Identification Number:	HTS 3104.20.0000	
Hazard Class:	Not applicable	
Proper Shipping Name	Not applicable	
Packing Group	Not applicable	
DOT Emergency Response Guide Number:	Not applicable	
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:	Not applicable	
MARPOL Annex V:	Non-HME	
IMO/IMDG:	Not applicable	

SECTION 15	REGULATORY INFORMATION		
CERCLA:	Not listed		
RCRA 261.33:	Not listed		
SARA TITLE III: (Exemptions at 40 CFR, Part 370 may apply for agricultural use, or for	Section 302/304: Not listed	RQ: No	TPQ: No
	Section 311/312:		



quantities of less than 10,000 pounds on-site.)	Acute: No	Chronic: No	Fire: No	Pressure: No	Reactivity: No
	Section 313: Not listed				
NTP, IARC, OSHA:	This material has not been identified as a carcinogen by NTP, IARC, or OSHA.				
Canada DSL and NDSL:	DSL: Yes NDSL: Not listed				
TSCA:	Listed on the TSCA Inventory				
CA Proposition 65: (Health & Safety Code Section 25249.5)	 WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov				
WHMIS:	WHMIS 2015 This SDS has been prepared according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR.				

SECTION 16	OTHER INFORMATION
Disclaimer:	<p>The information in this document is believed to be correct as of the date issued. HOWEVER, MOSAIC MAKES NO GUARANTEE, REPRESENTATION, OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO THE USE OF THIS PRODUCT. User is responsible for determining whether this product is fit for a particular purpose and suitable for user's method of use or application and assumes the risk of use thereof. The conditions and use of this product are beyond the control of Mosaic, and Mosaic disclaims any liability for loss or damage incurred in connection with the use or misuse of this product. Each user should review the recommended industrial hygiene and safe handling procedures in the specific context of the intended use and determine whether they are appropriate.</p>
Preparation:	The preparation of this SDS was in accordance with ANSI Z400.1-2010.
Revision Date:	March 24, 2020
Sections Revised:	1
SDS Number:	MOS 100052
References:	Globally Harmonized System of Classification and Labelling of Chemicals (GHS) – 4 th Edition 2011 OSHA Hazard Communication Standard, 2012 MARPOL Annex V; The Fertilizer Institute (TFI), 2003; TOXNET Toxline, Tomes, ECHA, OECD SIDS



Other Hazard Classifications:	NFPA HAZARD CLASS		HMIS HAZARD CLASS	
	Health:	1	Health:	1
	Flammability:	0	Flammability:	0
	Instability:	0	Physical Hazard:	0
	Special Hazard:	None	PPE:	Section 8
	WHMIS 2015 (HPR) HAZARD CLASS			
	Signal Word	N/A		
	Symbol	N/A		
	Classification	Not WHMIS Controlled		
	Hazard Statements	N/A		